



# T Series

# TR2 G-Build Engine

TR2

Power ranges: 11.0–14.4 kW; 14.8–19.3 bhp  
Fixed speeds: 1500, 1800 r/min

*Reliable, durable two-cylinder air-cooled G-Build diesel engine*

### Special Attributes

- ✓ suitable for generating sets
- ✓ designed for continuous operation in ambient temperatures up to 52 °C (122 °F)
- ✓ oil cooling by means of air flow over deep crankcase finning

### Basic Engine Characteristics

- diesel fuelled
- direct injection
- 2 cylinders
- air cooled
- naturally aspirated
- electric start (hand start optional)

### Design Features and Equipment

- medium-duty air cleaner\*
- inlet and exhaust manifolds
- self-vent fuel system with individual fuel injection pumps
- fuel filter
- fuel lift pump\*
- self-regulating plunger type lubricating oil pump
- spin-on lubricating oil filter
- decompressor lever
- flywheel with cooling fan
- flywheel housing with SAE4 flange
- mechanical governing
- 12V starter motor\*
- safety switches\*
- fuel control solenoid (energised to run)\*
- standard skid base packing
- 250 hour service intervals
- operators' handbook



### Emissions

Complies with EU Stage 3A exhaust emissions regulations.

### Optional Items

- 12V battery charge alternator

See also items with asterisk under *Design Features and Equipment*.


A range of options allows you to select a specification that matches your requirements; please consult your Lister Petter distributor.

\* Optional items standard on most builds.

**T Series: TR2 Engine Technical Data Sheet**

Power Outputs			
Power	r/min	1500	1800
Continuous	kW	11.0	13.1
	bhp	14.8	17.6
Intermittent (Fuel Stop)	kW	12.1	14.4
	bhp	16.2	19.3

Approximate Dimensions and Weight <sup>1</sup>		
Dry weight	kg	185
	lb	408
Length (A): no fuel tank	mm	571
	in	22.5
Width (B)	mm	521
	in	20.5
Height (C)	mm	683
	in	26.9



**Rating Definitions, to ISO 3046**

**ISO Standard Conditions**

Barometric pressure ..... 100 kPa  
 Relative humidity ..... 30%  
 Ambient temperature at air inlet manifold ..... 25°C

**Fixed speed power: continuous power (ICN)**

The power in kW which the engine is capable of delivering continuously at the stated crankshaft speed, under ISO standard conditions, measured at the flywheel without power-absorbing accessories, provided that the engine is overhauled and maintained in good operating condition and that fuel to BS EN 590 Class A1 or A2, and lubricating oils to the correct performance specification and viscosity classification as recommended by Lister Petter Limited, are used.

**Fixed speed power: overload power (ICXN)**

The maximum power in kW which the engine is capable of delivering intermittently at the stated crankshaft speed for a period not exceeding one hour in any period of twelve hours' continuous running, immediately after working at the continuous power, under ISO standard conditions and with the provisions specified for continuous power above.

**De-rating**

For non-standard site conditions, reference should be made to relevant BS, ISO and DIN standards.

**Notes:** 1. Power ratings measured at the flywheel apply to a fully run-in, non derated engine without power absorbing accessories or transmission equipment. 2. The overload capability applies to a fully run-in engine. This is normally attained after a running period of about 50 hours. 3. Excluding radiator.

Technical Data		
Type of fuel injection	Direct	
Number of cylinders	2	
Aspiration	Natural	
Direction of rotation looking on flywheel end	Anticlockwise	
Nominal cylinder bore	mm	98.42
	in	3.875
Stroke	mm	101.6
	in	4.0
Total cylinder capacity	litre	1.55
	in <sup>3</sup>	94.35
Compression ratio	15.5:1	
Minimum idling speed	r/min	850
Number of flywheel ring gear teeth	110	
Crankshaft end thrust (maximum continuous)	kgf	132
	lbf	290
Crankcase vacuum (minimum)	mbar	2.5
	in H <sub>2</sub> O	1.0
Crankcase vacuum (average)	mbar	4.6
	in H <sub>2</sub> O	1.8
Lubricating oil pressure (mean) with the oil at 110 °C (230 °F)	bar	2.0
	lbf ft <sup>2</sup>	29

**Distributor's Address**

Lister Petter have made efforts to ensure that the information in this data sheet is accurate but reserve the right to amend specifications and information without notice and without obligation or liability.



**UK**

Lister Petter Limited, Dursley, Gloucestershire  
 GL11 4HS England

Tel: +44 (0)1453 544141; fax: +44 (0)1453 546732

E-mail: sales@lister-petter.co.uk <http://www.lister-petter.co.uk>